

**NOTE:
SPECS:**

**PALLET DRAWING NOT TO SCALE.
PALLETIZATION: LEFT UP TO THE SUPPLIERS DISCRETION AS LONG AS IT DOES NOT EXCEED THE OVERALL SIZE OF PALLET.
FIDUCIALS TO BE 1.0mm ROUND AND PLACED ON OPPOSITE CORNERS OF THE PCB, ON BOTH SIDES OF THE CIRCUIT AND ON THE WEBBING AS INDICATED.**

SCORED .022" +/- .001" TOP, .022" +/- .001" BOTTOM. LEAVE NO MORE THAN .016" TO .018" IN THE CENTER


TOOLING HOLES ON EDGE OF PALLET TO BE .125 DIA TYP.

ALL OTHER SPECS TO BE BUILT TO IPC-D-275 PCB STANDARDS

0.300" WEBBING NEEDS TO BE ADDED TO ALL FOUR SIDES OF ANY PCB OR PALLET

AMI NOTE: MAXIMUM PALLET ARRAY MAY NOT BE INDICATIVE TO PROCESS.
PALLET ARRAY DEPENDANT ON GL AND THROUGHPUT.
SEE TECHNICAL SERVICES FOR ADVICE.

CUSTOMER: AMI



PALLET SPECS VISUAL

DESIGNED BY: MATT BROWN

PAGE 1 OF 1